

NEW

Winpact Chiller

Features

- · Compact design
- Overheat protection
- LED display with PID control of 0.1°C resolution
- Self-diagnosed abnormality function
- · Delayed resume compressor protection
- · Jetstream forced-flow circulation









The Winpact Chiller series is Major Science's newest addition to the bioprocessing technology portfolio to provide precise temperature control and excellent cooling performance for your fermentation needs and beyond. The recirculating chillers are compactly designed and require very little space; the built-on wheels offer an added bonus of mobility to any space-conscious labs. With a low procurement cost, it is your best option to stray away from costly tap water and is the perfect alternative for basic cooling needs.



Taiwan Office

No. 156, Sec. 1, Guoji Rd., Taoyuan Dist., Taoyuan City 330041, Taiwan T/+886-3-3762878 F/+886-3-3761310

US Office

19959 Sea Gull Way Saratoga, CA 95070 U.S.A. T/ +1-408-366-9866

F/ +1-408-446-1107

Shanghai Office

F/ +86-21-50795277

Room 612, International business exhibition center, 9300 Hunan Road, Pudong, Shanghai, China National toll-free No.:400-823-9177 T/ +86-21-50795277

D.No.7-143, 2nd Floor, St.No.2, Nagendra Nagar, Habsiguda, Hyderabad-500007.

T/ +91-40-27001515 T/ +91-40-27001586

India Office









Digital controller for easy operation

Specification

Cat. No.	WCC-100	WCC-101
Display	LED Display	
Temperature control	0°C to +100°C	
range		
Temperature stability	± 0.5 °C at 20 °C	
Temperature accuracy	± 0.5 °C at 20°C	
Controller	PID control, PT100 sensor	
Setting / display resolution	± 0.1°C	
Cooling capacity (Medium Ethanol)	1900 BTU/h @ 0°C	
Pump capacity flow rate (L/min)	5.5 L/min	
Hydraulic head	2.5 meter	
Pump capacity flow pressure (bar)	0.19 bar	
Pump connections	1/4" silicone tubing	
Barbed fittings diameter	6.35 mm or 1/4"	
(inner dia. / mm)	3.33 3	
Bath capacity	10 L	
Refrigerant	CFC free refrigerants-R134a	
Operating temperature	+20°C~+40°C	
Operating humidity	Max.80%	
Rated voltage	110V; 60Hz, 14.5A	220V; 50Hz, 8A
Chamber material	304 stainless steel	
Bath inner dimension	(W x L x H) 9.25"x11.61"x5.90" (235x295x150 mm)	
External material	Powder coating	
Compressor	1/4 HP	
Dimension	(W x L x H) 13.39"x22.04"x26.38" (340x560x670 mm)	
Weight	Approx. 110.2 lb (50 kg)	
	- Self-diagnosed abnormality display	
- Electronic overheating thermal fuse protection		'
	increments of 0.1°C	
	- Delayed resume compressor protection	
Circulation volume	Cycles up to 5.5 L/min cooling system with delayed resume protection after power outage	
Circulation type	Jet stream flow forced circulation, can be accessed through	
Circulation type	the outer loop	
Power	1000W	

Ordering Information

Cat. No.	Product Description
WCC-100	Winpact Chiller, 110V
WCC-101	Winpact Chiller, 220V

^{*} All images are for reference only, actual products might differ from the pictures above.

^{*} Technical specifications subject to change without notice.