



Winpact CO₂ resistant orbital shaker, WP-COS

- Winpact
- Corrosion-resistant construction protects internal components from high CO₂ and humidity.
- Compact design enables use inside a CO₂ incubator for versatile applications.
- Platform supports multiple accessories, including flask clamps and tube racks, to accommodate lab labware.
- Variable speed range of 1–300 rpm ensures smooth shaking.
- 12" touch screen for intuitive operation.

Cat. No.	WP-COS
Speed	0, 1 to 300 rpm (1 rpm step)
Motor	Brushless motor
Top Plate Material	316L
Capacity	Max. 5kg
Controller	12" color touch panel
Mode	Continuous / Timing / Programable
Voltage	AC 100-240V, 50/60Hz
Dimensions	Controller: 320 x 102 x 246 mm
(W x L x H)	Base : approx. 310 x 310 x 97 mm
	(including tray platform)
Weight	Controller : approx. 4.65kg / Base : approx. 7.15kg

Cat. No.	Product Description
WP-COS	CO ₂ resistant orbital shaker with
	12" colorful touch screen
WP-12-TC-CONTROL	12" colorful touch screen
WP-COS-BASE	Shaker base unit of Tetrad Slow Speed
	Magnetic Stirrer with 12" colorful touch screen
WP-12-TC-CABLE	Ribbon Cable set for 12" colorful
	touch screen use





9999 [©]

1/10 4

U.S.A. T/ +1-408-366-9866 F/ +1-408-446-1107

US Office

Shanghai Office

Building #C1, 880, JiangYang Nan Road, Baoshan,Shanghai, china 200439

Taiwan Office

No. 156, Sec. 1, Guoji Rd., Taoyuan Dist., Taoyuan City 330041, Taiwan T/+886-3-3762878 F/+886-3-3761310

India Office

D.No.7-143, 2nd Floor, St.No.2,Nagendra Nagar, Habsiguda, Hyderabad-500007. India T/ +91-40-27001515 T/ +91-40-27001586

Tel:13585666474

